



... your business allies



The-ma SpA

PORDENONE

V.le Lino Zanussi, 6/C - 33170 Pordenone (PN) Italy  
Tel. +39 0434 572677 - Fax: +39 0434 572686

PADOVA

Via Col. A. Varisco, 22/A - 35010 Peraga di Vigonza (PD) Italy  
Tel. +39 049 725499 - Fax: +39 049 8932615

BOLOGNA

Via della Repubblica, 8 - 40061 Minerbio (BO)  
Tel. +39 051 873587 - Fax: +39 051 6621778

[www.the-ma.it](http://www.the-ma.it) - [info@the-ma.it](mailto:info@the-ma.it)

Foam rubbers

Compact rubbers

# Foams

Soundproofing





... your business allies

Adhesives and sealants  
Transformation and die-cutting

# TECHNICAL FOAMS



## TH130EP EPDM

Density	120 ± 20 kg/m <sup>3</sup>
Temperature use	-40/+70°C constant
Thicknesses	From 2 to 50 mm





## TH240BI EPDM

Density	140 kg/m <sup>3</sup>
Temperature use	-40/+80°C constant
Thicknesses	From 2 to 40 mm





## TH29LD Polyethylene foam

Density	29 kg/m <sup>3</sup>
Temperature use	-70/+105°C constant
Thicknesses	From 2 to 50 mm





## TH45LD Polyethylene foam

Density	45 kg/m <sup>3</sup>
Temperature use	-70/+110°C constant
Thicknesses	From 2 to 30 mm





## TH35PEQ Polyethylene foam

Density	37 ± 5 kg/m <sup>3</sup>
Temperature use	100°C constant
Thicknesses	From 2 to 100 mm



## TH30PX Coloured polyethylene foam

Density	33 ± 4 kg/m <sup>3</sup>
Temperature use	100°C constant
Thicknesses	From 2 to 100 mm



## TH45EV Vinyl ethylene acetate

Density	45 ± 6 kg/m <sup>3</sup>
Temperature use	-40/+60°C constant
Thicknesses	From 2 to 100 mm

## TH100EV E.V.A. + PE foam

Density	85/90 kg/m <sup>3</sup>
Temperature use	-10/+70°C constant
Thicknesses	From 2 to 40 mm

## TH120PV PVC foam

Density	120 kg/m <sup>3</sup>
Temperature use	-20/+60°C
Thicknesses	From 2 to 20 mm

## TH20XNR Non cross-linked polyethylene foam

Density	18/20 kg/m <sup>3</sup>
Temperature use	-20/+70°C
Thicknesses	From 10 to 100 mm

## TH18CDH Polyurethane foam


Density	17.3 kg/m <sup>3</sup>
Strength compression	4.2 kPa
Thicknesses	From 3 to 100 mm

## TH10PPI Cross-linked polyurethane filter

Density	27/31 kg/m <sup>3</sup>
Diameter cell	3800/5002 μm
Thicknesses	From 3 to 100 mm



Coloured TH100EV



TH130EP Profiles



TH130EP Rolls



Die cutting and punching processing

Milling and cutting processing

Milling and cutting processing

